

In accordance with annex III of Regulation (EU) 305/2011

No. FTL031 CE 2797 CPR 530942

Monolevel RM

1. Unique identification code of the product type:

EN 998-1 One coat render (OC).

2. Type, batch or serial number of any other element allowing identification of the construction product as required under Article 11(4):

See batch number and date of manufacture on packaging.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

One coat spray/float applied render for external and internal application to walls, soffits and columns.

4. Name, registered trade mark and contact address of manufacturer as required pursuant Article 11(5):

Flexcrete Technologies Limited
Tomlinson Road, Leyland
Lancashire, PR25 2DY

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable.

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 998-1

Reaction to fire has been assessed and determined by type testing carried out by notified test laboratory 0833 under System 3.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable.

9. Declared Performance:

| Essential Characteristics | Performance | Test Standard | hEN Standard |
|--|--|---------------|-------------------|
| Dry Bulk Density | 1900-1950 kg.m ³ | EN 1015-10 | EN 998-1: 2010 |
| Compressive Strength | CSIV: ≥ 6MPa | EN 1015-11 | |
| Adhesion after Weathering Cycles | > 2.0MPa FP B/C Strong Substrate > 0.4MPa FP C Weak substrate | EN 1015-21 | |
| Capillary Absorption | W2: ≤ 0.2kg.m ⁻² .min ^{-0.5} | EN 1015-18 | |
| Water permeability on relevant substrates after weathering | ≤ 1ml.cm ⁻² .48h ⁻¹ | EN 1015-21 | |
| Water Vapour permeability coefficient | μ < 15 | EN 1015-19 | |
| Reaction to Fire | Euroclass A2-s1, d0 | EN 13501-1 | |

10. Declaration:

The performance of the product identified above is in conformity with the set of declared performance in Section 9. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above in Section 4.

Signed for and on behalf of the manufacturer by:



Paul Hutton - Technical Manager
Revision 4 - Leyland 01/12/22