

The Construction Products EU Exit Regulations 2020 No. 1359

No. FTL035 UKCA 0086 CPR 753276

Monodex ICB

1. Unique identification code of the product type:

BS EN 1504-2:2004 Surface Protection System.

2. Type, batch or serial number of any other element allowing identification of the construction product as required under Article 11(4):

See batch number and date of manufacture on packaging.

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

Waterproof intermediate crack bridging filler and coating for protection against ingress (PIC).

4. Name, registered trade mark and contact address of manufacturer as required pursuant Article 11(5):

Flexcrete Technologies Limited
Tomlinson Road, Leyland
Lancashire, PR25 2DY

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable.

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

BS EN 1504-2

The UK Approved Body 0086 undertook the initial inspection of type testing, manufacturing plant, factory production control and the continuous surveillance, assessment and evaluation of factory production control under System 2+ and issued Certificate of Conformity of factory production control.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable.

9. Declared Performance:

Essential Characteristics	Performance	Test Standard	Designated Standard
Permeability to CO ₂	S _D > 50m (R)	BS EN 1062-6	BS EN 1504-2: 2004
Permeability to Water Vapour	S _D < 5m (Class I: Permeable to water vapour)	BS EN ISO 7783-2	
Capillary Absorption	w < 0.1 kg.m ⁻² h ^{-0.5} (Class III)	BS EN 1062-3	
Adhesive Bond	≥ 0.8 MPa (Crack bridging or flexible systems without trafficking)	BS EN 1542	
Artificial Weathering	No change after 5000 hours	BS EN 1062-11	
Static Crack Bridging	Static > 500µm (Class A3)	BS EN 1062-7	
Dangerous Substances	COMPLIES	CLAUSE 5.4	
Reaction to Fire	Euroclass F	BS EN 13501-1	

10. Declaration:

The performance of the product identified above is in conformity with the set of declared performance in Section 9. This declaration of performance is issued, in accordance with The Construction Products (Amendment etc.) (EU Exit) Regulations 2020 No.1359, under the sole responsibility of the manufacturer identified above in Section 4.

Signed for and on behalf of the manufacturer by:



Paul Hutton - Technical Manager
Leyland 01/12/22