Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830. - United Kingdom (UK)

SAFETY DATA SHEET

Cemprotec E942 Part A

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name

: Cemprotec E942 Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Professional application of coatings and inks		
Uses advised against	Reason	
All Other Uses		

1.3 Details of the supplier of the safety data sheet

International Farg AB Holmedalen 3 Aspereds Industriomrade SE-424 22 Angered Sweden

Tel: +46 (0) 31 928500 Fax: +46 (0) 31 928530

e-mail address of person : sdsfellinguk@akzonobel.com responsible for this SDS National contact

1.4 Emergency telephone number

National advisory body/Poison Centre (For use only by licensed medical professionals.)Telephone number: +44 (0)844 892 0111SupplierTelephone number: +46 8 33 12 31

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412 The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements



SECTION 2: Hazards identification

Hazard pictograms	
Signal word	: Warning
Hazard statements	 Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Wear protective gloves. Wear eye or face protection. Avoid release to the environment.
Response	: IF ON SKIN: Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	 Phenol, polymer with formaldehyde, glycidyl ether reaction product: bisphenol-A-(epichlorhydrin); epoxy resin 1,2-benzisothiazol-3(2H)-one
Supplemental label elements	: Contains epoxy constituents. May produce an allergic reaction.
	Wear appropriate respirator when ventilation is inadequate.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.

2.3 Other hazards		
Other hazards which do	:	None known.
not result in classification		

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	% by weight	<u>Classification</u> Regulation (EC) No. 1272/2008 [CLP]	Nota (s)	Туре
Phenol, polymer with formaldehyde, glycidyl ether	CAS: 28064-14-4	≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin	REACH #: 01-2119456619-26 EC: 500-033-5 CAS: 25068-38-6 Index: 603-074-00-8	≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
1,2-benzisothiazol-3 (2H)-one	EC: 220-120-9 CAS: 2634-33-5	≤0.025	Acute Tox. 4, H302 Skin Irrit. 2, H315	-	[1]
Date of issue/Date of revision Version 3	25/04/2017	2/13		AkzoN	lobel

Date of issue/Date of revision Version : 3

SECTION 3: Composition/information on ingredients

-	0
Index: 613-088-00-6	Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
	See Section 16 for the full text of the H statements declared above.

X.International.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

Version : 3

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

	Nota (s)
SECTION 4: First aid measures	

4.1 Description of first aid measures

General	:	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	:	If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effect	2			
Eye contact	: Causes serious eye irritation.			
Inhalation	: No known significant effects or critical hazards.			
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.			
Ingestion	: Irritating to mouth, throat and stomach.			
Over-exposure signs/symptoms				
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness			
Inhalation	: No specific data.			
Skin contact	 Adverse symptoms may include the following: irritation redness 			
Ingestion	: No specific data.			
Date of issue/Date of revision	: 25/04/2017			

3/13

SECTION 4: First aid measures

4.3 Indication of any immedia	te medical attention and special treatment needed
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
SECTION 5: Firefight	ing measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising fr	om the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters	
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, prot	ective equipment and emergency procedures	
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.	
6.3 Methods and material for containment and cleaning up		
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	



SECTION 6: Accidental release measures

Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

. .

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.



SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures		f this product contains ingredients with exposure limits, per atmosphere or biological monitoring may be required to def of the ventilation or other control measures and/or the nece protective equipment. Reference should be made to monit the following: European Standard EN 689 (Workplace atm he assessment of exposure by inhalation to chemical ager imit values and measurement strategy) European Standar atmospheres - Guide for the application and use of procedu of exposure to chemical and biological agents) European Standar Workplace atmospheres - General requirements for the per or the measurement of chemical agents) Reference to na locuments for methods for the determination of hazardous equired.	termine the effectiveness essity to use respiratory oring standards, such as ospheres - Guidance for hts for comparison with rd EN 14042 (Workplace ures for the assessment Standard EN 482 erformance of procedures tional guidance
DNELs/DMELs			
No DNELs/DMELs available	e.		
PNECs			
No PNECs available			
8.2 Exposure controls			
Appropriate engineering controls	:	Good general ventilation should be sufficient to control wor contaminants.	ker exposure to airborne
Individual protection measured			
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling before eating, smoking and using the lavatory and at the e Appropriate techniques should be used to remove potentia Contaminated work clothing should not be allowed out of the contaminated clothing before reusing. Ensure that eyewas showers are close to the workstation location.	nd of the working period. ally contaminated clothing. he workplace. Wash
Eye/face protection	:	Safety eyewear complying with an approved standard shoun assessment indicates this is necessary to avoid exposure gases or dusts. If contact is possible, the following protect unless the assessment indicates a higher degree of protect goggles.	to liquid splashes, mists, tion should be worn,
Skin protection			
Hand protection	:	Use chemical resistant gloves classified under Standard E against chemicals and micro-organisms. Recommended: gloves. When prolonged or frequently repeated contact m protection class of 6 (breakthrough time greater than 480 r 374) is recommended. When only brief contact is expected protection class of 2 or higher (breakthrough time greater that according to EN 374) is recommended. The user must ch of type of glove selected for handling this product is the mointo account the particular conditions of use, as included in assessment. NOTICE: The selection of a specific glove for and duration of use in a workplace should also take into account protection as, but not limited to: Other chemic handled, physical requirements (cut/puncture protection, d protection), potential body reactions to glove materials, as specifications provided by the glove supplier. Barrier creat the exposed areas of the skin but should not be applied or occurred.	Viton® or Nitrile ay occur, a glove with a minutes according to EN d, a glove with a than 30 minutes eck that the final choice ost appropriate and takes the user's risk or a particular application ccount all relevant cals which may be exterity, thermal well as the instructions/ ms may help to protect
Body protection	:	Personal protective equipment for the body should be sele being performed and the risks involved and should be app before handling this product.	
Other skin protection	:	Appropriate footwear and any additional skin protection me selected based on the task being performed and the risks approved by a specialist before handling this product.	
Date of issue/Date of revision		: 25/04/2017	AkzoNobol



X.International.

SECTION 8: Exposure controls/personal protection

Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

X.International.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

		na enemiea propertiee
<u>Appearance</u>		
Physical state	:	Liquid.
Colour	:	White.
Odour	:	Mild.
Odour threshold	:	Not available.
рН	:	Not applicable.
Melting point/freezing point	:	Not available.
Initial boiling point and boiling range	:	Lowest known value: 100°C (212°F) (water).
Flash point	:	Closed cup: Not applicable.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Upper/lower flammability or explosive limits	:	Not available.
Vapour pressure	:	Not available.
Vapour density	:	Not available.
Relative density	:	1.032
Solubility(ies)	:	Insoluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (room temperature): 100 mm ² /s
Explosive properties	:	Not available.
Oxidising properties	:	Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity				
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: No specific data.			
10.5 Incompatible materials	: No specific data.			
Date of issue/Date of revision Version : 3	: 25/04/2017 AkzoNobel			

SECTION 10: Stability and reactivity

XInternational

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,2-benzisothiazol-3(2H)-	LD50 Oral	Rat	1020 mg/kg	-
one				

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction product: bisphenol- A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 microliters	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
1,2-benzisothiazol-3(2H)-one	Skin - Mild irritant	Human	-	48 hours 5 Percent	-
Conclusion/Summary	: Not available.				
<u>Sensitisation</u>					
Conclusion/Summary	: Not available.				
<u>Mutagenicity</u>					
Conclusion/Summary	: Not available.				
<u>Carcinogenicity</u>					
Conclusion/Summary	: Not available.				
<u>Reproductive toxicity</u>					
Conclusion/Summary	: Not available.				
<u>Teratogenicity</u>					
Conclusion/Summary	: Not available.				
Specific target organ toxicity	<u>/ (single exposure)</u>				
Not available.					
<u>Specific target organ toxicity</u> Not available.	<u>/ (repeated exposure)</u>				
<u>Aspiration hazard</u> Not available.					
nformation on likely routes f exposure	: Not available.				
otential acute health effects					
Eye contact	: Causes serious eye irritation	on.			
Inhalation	: No known significant effect	ts or critical hazar	rds.		
Skin contact	: Causes skin irritation. May	/ cause an allergi	c skin rea	iction.	
Ingestion	: Irritating to mouth, throat a	nd stomach.			
ate of issue/Date of revision	: 25/04/2017			Δ	kzoNobel

Date of issue/Date of revision Version : 3



SECTION 11: Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

<u>Short term exposure</u>		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Long term exposure		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Potential chronic health effe		
Not available.		
Conclusion/Summary	Not available.	
General	Once sensitized, a severe allergic reaction may occur when subsequently expose to very low levels.	ed
Carcinogenicity	No known significant effects or critical hazards.	
Mutagenicity	No known significant effects or critical hazards.	
Teratogenicity	No known significant effects or critical hazards.	
Developmental effects	No known significant effects or critical hazards.	
Fertility effects	No known significant effects or critical hazards.	

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
1,2-benzisothiazol-3(2H)-one	Acute EC50 1.5 mg/l	Daphnia - Daphnia magna	48 hours
	Acute EC50 97 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute IC50 0.067 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute LC50 >10 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 1.3 mg/l	Fish - Ochorhyncus mykiss	96 hours
	Acute LC50 167 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours

12.2 Persistence and degradability

Conclusion/Summary : Not available.



K.International.

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
reaction product: bisphenol- A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
reaction product: bisphenol- A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	2.64 to 3.78	-	low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment		
PBT	: Not applicable.	
vPvB	: Not applicable.	

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	 The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

Waste code	Waste designation	
08 02 99	wastes not otherwise specified	

Packaging

Methods of disposal	:
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

:



SECTION 14: Transport information

		INDO	1474
	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	-

IMDG Code Segregation : Not applicable. group

14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk: Not available.according to Annex II ofMarpol and the IBC Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex AIV - LIST OF SUDStances Sub
Annex XIV
Substances of very high concern
None of the components are listed.
Annex XVII - Restrictions : Not a
on the manufacture,
placing on the market
and use of certain
dangerous substances,
mixtures and articles
Other EU regulations

Other EU regulations

Europe inventory

: Not determined.

Not applicable.

Special packaging requirements

Containers to be fitted : Not applicable. with child-resistant fastenings

Tactile warning of danger : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

AkzoNobel

SECTION 15: Regulatory information

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

National regulations

- References
 : Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II and Regulation (EC) No. 1272/2008 (CLP)
- **15.2 Chemical safety** : No Chemical Safety Assessment has been carried out.

assessment

X.International.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classific	Justification	
Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412	Calculation method Calculation method Calculation method Calculation method	
Full text of abbreviated H statements	02Harmful if swallowed.15Causes skin irritation.17May cause an allergic skin reaction.18Causes serious eye damage.19Causes serious eye irritation.00Very toxic to aquatic life.10Very toxic to aquatic life with long lasting effects.12Harmful to aquatic life with long lasting effects.	
Full text of classifications [CLP/GHS]	ute Tox. 4, H302 uatic Acute 1, H400 uatic Chronic 1, H410 uatic Chronic 2, H411 uatic Chronic 3, H412 e Dam. 1, H318ACUTE TOXICITY (oral) - Category 4 ACUTE AQUATIC HAZARD - Category 1 LONG-TERM AQUATIC HAZARD - Category LONG-TERM AQUATIC HAZARD - Category LONG-TERM AQUATIC HAZARD - Category SERIOUS EYE DAMAGE/ EYE IRRITATION - 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - 2 SKIN CORROSION/IRRITATION - Category 1	2 3 Category Category
Date of printing	04/2017	
Date of issue/ Date of revision	04/2017	
Date of previous issue	06/2016	
Version		
Notice to reader		

12/13

:

SECTION 16: Other information

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be). © AkzoNobel



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830. - United Kingdom (UK)

SAFETY DATA SHEET

Cemprotec E942 Part B

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name

: Cemprotec E942 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Professional application of coatings and inks		
Uses advised against	Reason	
All Other Uses		

1.3 Details of the supplier of the safety data sheet

	5		
Flexcrete Technologies Ltd. Tomlinson Road Leyland Lancashire, United Kingdom PR25 2DY			
Tel: +44(0)1772 450950			
e-mail address of person responsible for this SDS	: sdsfellinguk@akzonobel.com		
National contact			
1.4 Emergency telephone number			
National advisory body/Pois	on Centre (For use only by licensed medical professionals.)		
Telephone number	: +44 (0)344 892 0111 (UK) +353 (0)1 809 2566 (Eire)		
<u>Supplier</u>			
Telephone number	: +44 (0)191 469 6111 (24H)		

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

AkzoNobel

SECTION 2: Hazards identification

Hazard pictograms	
Signal word	: Danger
Hazard statements	: Causes serious eye damage. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.
Precautionary statements	
General	: Not applicable.
Prevention	: Wear protective gloves. Wear eye or face protection. Use only outdoors or in a well-ventilated area.
Response	: IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN: Take off contaminated clothing and wash it before reuse. IF IN EYES: Immediately call a POISON CENTER or physician.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	: Cement, portland, chemicals
Supplemental label elements	:
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.

X.International.

2.3 Other hazards	
Other hazards which do	: None known.
not result in classification	

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

name	Identifiers	% by weight	Regulation (EC) No. 1272/2008 [CLP]	Nota (s)	Туре
Cement, portland, chemicals	EC: 266-043-4 CAS: 65997-15-1	≥10 - ≤25	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335	-	[1] [2]
crystalline silica	EC: 238-878-4 CAS: 14808-60-7	≥10 - ≤25	Not classified.	-	[2]
glass, oxide, chemicals	EC: 266-046-0 CAS: 65997-17-3	≤3	Not classified.	-	[2]
itanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤3	Not classified.	-	[2]
calcium dihydroxide	EC: 215-137-3	≤3	Skin Irrit. 2, H315	-	[1] [2]

Version : 7

XInternational.

SECTION 3: Composition/information on ingredients CAS: 1305-62-0 Eve Irrit, 2, H319 **STOT SE 3. H335** Aquatic Chronic 3, H412 [1] Ox. Sol. 3. H272 sodium nitrite REACH #: <1 01-2119471836-27 Acute Tox. 3. H301 EC: 231-555-9 Eve Irrit. 2, H319 CAS: 7632-00-0 Aquatic Acute 1, H400 (M=10) Index: 007-010-00-4 Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.	
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.	
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Seek medical attention.	
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Seek medical attention if irritation persists. Do NOT use solvents or thinners.	
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health ef	fects		
Eye contact	: Causes serious eye damage.		
Inhalation	: May cause respiratory irritation.		
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.		
Ingestion	: Irritating to mouth, throat and stomach.		
<u>Over-exposure signs/sy</u>	nptoms		
Eye contact	: Adverse symptoms may include the following: pain watering redness	pain watering	
Date of issue/Date of revision	: 15/05/2019	AkzoNobel	
Version 17			

X.International.

SECTION 4: First aid measures

Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	: None known.	
5.2 Special hazards arising fi	the substance or mixture	
Hazards from the substance or mixture	No specific fire or explosion hazard.	
Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides metal oxide/oxides	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	
decomposition products 5.3 Advice for firefighters Special protective actions for fire-fighters Special protective	carbon dioxide carbon monoxide sulfur oxides metal oxide/oxides Promptly isolate the scene by removing all persons from the vicinity of the incide there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection	

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures For non-emergency : No action shall be taken involving any personal risk or without suitable training

personnel	Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

15/05/2019

:



SECTION 6: Accidental release measures

6.3 Methods and material f	or containment and cleaning up
Small spill	: Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	 Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)		
Recommendations	: Not available.	
Industrial sector specific	: Not available.	
solutions		

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits



X.International.

SECTION 8: Exposure controls/personal protection

 of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such a the following: European Standard EN 689 (Workplace atmospheres - Guidance fo the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 4402 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical agents) European Standard EN 4402 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required. DNELs/DMELS No DNELs/DMELs available. PNECS No PNECs available Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or ther engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Individual protection measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eye/face protection Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mist gases or dusts. Use eye protection according te Hollowing protection should be worn, unless the assessment indicates as higher degree of protection. 	Product/ingredient name		Exposure limit values
TWA: 0.1 mg/m ² 8 hours. Form: respirable dust glass, oxide, chemicals titanium dioxide EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 10 mg/m ² 8 hours. Form: inhalable dust calcium dihydroxide EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 10 mg/m ² 8 hours. Form: inhalable dust calcium dihydroxide Recommended monitoring procedures if this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectivenees of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such a the following: European Standard EN 4680 (Workplace atmospheres - Guide to the application and use of procedures for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy). European Standard EN 4422 (Workplace atmospheres - Guide to the application and use of procedures for the assessment of exposure to chemical agents for the performance of procedure for the measurement of chemical agents). European Standard EN 4422 (Workplace atmospheres - Guide to the termination of hazardous substances will also be required. DNELs/DMELs No DNELs/DMELs available. 212 Exposure controls Appropriate engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Individual protection measures Wash hands, forearms	Cement, portland, chemicals		TWA: 10 mg/m ³ 8 hours. Form: inhalable dust
titanium dioxide TWA: 5 mg/m³ 8 hours. titanium dioxide EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 10 mg/m³ 8 hours. Form: inhalable dust TWA: 4 mg/m³ 8 hours. Form: inhalable dust calcium dihydroxide EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 5 mg/m³ 8 hours. TWA: 5 mg/m³ 8 hours. Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectivenes of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such a the following: European Standard EN 469 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 4482 (Workplace atmospheres - Guida of the departs) Reference to national guidance documents for methods for the determination of hazardous substances will also be required. DNELs/DMELs No DNELs/DMELs available. PECS No PNECs available :2 Exposure controls Appropriate engineering controls to keep workre exposure to airborne contaminants below any recommended or statutory limits. Hygione measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period contaminated cothing before reating. Smoking and using the lavatory and at the end of	crystalline silica		
Calcium dihydroxide TWA: 10 mg/m³ 8 hours. Form: respirable dust TWA: 4 mg/m³ 8 hours. Form: respirable dust TWA: 4 mg/m³ 8 hours. Form: respirable dust Recommended monitoring : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectivenes of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such a the following: European Standard EN 469 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 462 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical agents). European Standard EN 462 (Workplace atmospheres - Guide for the determination of hazardous substances will also be required. DNELs/DMELs No DNELs/DMELs available. No PNECs available : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to althome contaminants below any recommended or statutory limits. Individual protection measures : Wash hands, forearms and face thoroughy after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to the workplace antispheres in clausing should not be allowed out of the workplace antispheres in gases or dusts. Use eye protection according to the workplace antispheres inguis gasses or dusts. Use eye sever a coroleying	glass, oxide, chemicals		• • • •
TWA: 5 mg/m³ 8 hours. Recommended monitoring procedures If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectivenes of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such a the following: European Standard EN 689 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy). European Standard EN 482 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents). European Standard EN 482 (Workplace atmospheres - Guide for the application and use of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required. DNELs/DMELs No DNELs/DMELs available. 22 Exposure controls Appropriate engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Individual protection measures I Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working perior Contaminate dothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eye/face protection Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists gagaes or dusts. Use eye relection according to	titanium dioxide		TWA: 10 mg/m ³ 8 hours. Form: inhalable dust
proceduresatmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such a the following: European Standard EN 689 (Workplace atmospheres - Guidance fo the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 1422 (Workplace atmospheres - General requirements for the performance of procedure for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.DNELs/DMELs No DNELs/DMELs availableUse only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.Individual protection measuresWash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to remove potentially contaminated clothin Contaminated work clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.Eye/face protectionSafety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists gases or dusts. Use eye protection according to EN 166, designed to protect against	calcium dihydroxide		
DNELs/DMELs No DNELs/DMELs available. PNECs No PNECs available 2.2 Exposure controls Appropriate engineering controls : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Individual protection measures Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to remove potentially contaminated clothin Contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eye/face protection Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists gases or dusts. Use eye protection according to EN 166, designed to protect against liquid splashes. If contact is possible, the following protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirato may be required instead.	procedures atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical agents) European Standard EN 482 (Workplace atmospheres - Guide for the application and use of procedures for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be		
No PNECs available B:2 Exposure controls Appropriate engineering controls : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Individual protection measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to remove potentially contaminated clothin Contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists gases or dusts. Use eye protection according to EN 166, designed to protect against liquid splashes. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.	No DNELs/DMELs available		
 Appropriate engineering controls Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Individual protection measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eye/face protection Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists gases or dusts. Use eye protection according to EN 166, designed to protect against liquid splashes. If contact is possible, the following protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. 			
 Appropriate engineering controls Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Individual protection measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eye/face protection Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists gases or dusts. Use eye protection according to EN 166, designed to protect against liquid splashes. If contact is possible, the following protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. 	3.2 Exposure controls		
 Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to remove potentially contaminated clothin Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eye/face protection Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists gases or dusts. Use eye protection according to EN 166, designed to protect against liquid splashes. If contact is possible, the following protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. 	Appropriate engineering controls	vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any	
 before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to remove potentially contaminated clothin Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eye/face protection Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists gases or dusts. Use eye protection according to EN 166, designed to protect against liquid splashes. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. 			
assessment indicates this is necessary to avoid exposure to liquid splashes, mists gases or dusts. Use eye protection according to EN 166, designed to protect against liquid splashes. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.	Hygiene measures	before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety	
	Eye/face protection	against liquid splashes. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator	



SECTION 8: Exposure controls/personal protection

Hand protection	: Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/ specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.EN ISO 13688
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	:	Solid. [powder]
Colour	:	Grey.
Odour	:	Odourless.
Odour threshold	:	Not available.
рН	:	Not applicable.
Melting point/freezing point	:	Not available.
Initial boiling point and boiling range	:	Not available.
Flash point	:	Closed cup: 101°C
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Upper/lower flammability or explosive limits	:	Not available.
Vapour pressure	:	Not available.
Vapour density	:	Not available.
Relative density	:	2.66
Solubility(ies)	:	Soluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Date of issue/Date of revision	:	15/05/2019
Version : 7		7/13

AkzoNobel

K.International.

SECTION 9: Physical and chemical properties

Viscosity	: Kinematic (room temperature): 999.1 mm ² /s
Explosive properties	: Not available.
Oxidising properties	: Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity		
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.	
10.2 Chemical stability	: The product is stable.	
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	: No specific data.	
10.5 Incompatible materials	: No specific data.	
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
calcium dihydroxide	LD50 Oral	Rat	7340 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

	Route	ATE value
Oral		20325.2 mg/kg

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
calcium dihydroxide	Eyes - Severe irritant	Rabbit	-	10 milligrams	-
sodium nitrite	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
Conclusion/Summary	: Not available.	·			
<u>Sensitisation</u>					
Conclusion/Summary	: Not available.				
<u>Mutagenicity</u>					
Conclusion/Summary	: Not available.				
Carcinogenicity					
Conclusion/Summary	: Not available.				
Reproductive toxicity					
Conclusion/Summary	: Not available.				
<u>Teratogenicity</u>					
Conclusion/Summary	: Not available.				
Specific target organ toxicit	<u>y (single exposure)</u>				

15/05/2019

AkzoNobel

XInternational.

X.International.

SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
Cement, portland, chemicals	Category 3	Not applicable.	Respiratory tract irritation
calcium dihydroxide	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes	:	Not available.
of exposure		

Potential acute health effects

Eye contact	: Causes serious eye damage.
Inhalation	: May cause respiratory irritation.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.

:

15/05/2019



SECTION 11: Toxicological information

Developmental effects Fertility effects : No known significant effects or critical hazards.

: No known significant effects or critical hazards.

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
calcium dihydroxide	Acute LC50 33884.4 µg/l Fresh water	Fish - Clarias gariepinus -	96 hours
		Fingerling	
sodium nitrite	Acute EC50 159000 µg/l Marine water	Algae - Tetraselmis chuii	72 hours
	Acute EC50 1600000 µg/l Marine water	Algae - Tetraselmis chuii	96 hours
	Acute LC50 1100 µg/l Fresh water	Crustaceans - Cherax	48 hours
		quadricarinatus	
	Acute LC50 48 μg/l Fresh water	Fish - Ictalurus punctatus - Fingerling	96 hours
	Chronic NOEC 0.912 mg/l Marine	Fish - Hippocampus	35 days
	water	abdominalis - Juvenile (Fledgling, Hatchling, Weanling)	

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
sodium nitrite	-3.7	-	low

12.4 Mobility in soil	
Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

- **PBT** : Not applicable.
- vPvB : Not applicable.
- **12.6 Other adverse effects** : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	 The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
European waste catalog	<u>gue (EWC)</u>



SECTION 13: Disposal considerations

Code number	Waste designation			
EWC 17 01 06*	mixtures of, or separate fractions of concrete, bricks, tiles and ceramics containing hazardous substances			
Packaging				
Methods of dispose	 Dispose of containers contaminated by the product in accordance with local or national legal provisions. This material and its container must be disposed of as hazardous waste. Dispose of via a licensed waste disposal contractor. 			
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.			

XInternational.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	The environmentally hazardous substance mark may appear if required by other transportation regulations.

IMDG Code Segregation : Not applicable. group

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in user the event of an accident or spillage.

14.7 Transport in bulk : Not available. according to Annex II of Marpol and the IBC Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

Substances of very high concern

None of the components are listed.



SECTION 15: Regulatory information

SECTION 15. Regula		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Other EU regulations		
Europe inventory	:	Not determined.
Special packaging requirem	ien	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
Ozone depleting substance	es	<u>(1005/2009/EU)</u>
Not listed.		
Prior Informed Consent (P	IC)	(649/2012/EU)
Not listed.		
National regulations		
References	:	Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II and Regulation (EC) No. 1272/2008 (CLP)
15.2 Chemical safety assessment	:	No Chemical Safety Assessment has been carried out.
SECTION 16: Other in	nfo	ormation
Indicates information that h	as	changed from previously issued version.
Abbreviations and	:	ATE = Acute Toxicity Estimate
acronyms		CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level

1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification		Justification
Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335		Calculation method Calculation method Calculation method Calculation method
Full text of abbreviated H : H272 statements H301 H315 H317 H318 H319 H335 H400 H411 H412		May intensify fire; oxidiser. Toxic if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. May cause respiratory irritation. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.



X.International.

SECTION 16: Other information

Full text of classifications [CLP/GHS]	:	Acute Tox. 3, H301 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 Aquatic Chronic 3, H412 Eye Dam. 1, H318 Eye Irrit. 2, H319 Ox. Sol. 3, H272 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335	ACUTE TOXICITY (oral) - Category 3 ACUTE AQUATIC HAZARD - Category 1 LONG-TERM AQUATIC HAZARD - Category 2 LONG-TERM AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 OXIDIZING SOLIDS - Category 3 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Date of printing	:	15/05/2019	
Date of issue/ Date of revision	:	15/05/2019	
Date of previous issue	:	15/05/2019	
Version	:	7	

Notice to reader

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be). © AkzoNobel

